

Xk 21086 SFP B H

Electric Mortise Door Release



Description

This universal model is suitable for most mortise door locks. The keep is 4mm adjustable to the constructional circumstances. Because the strike case is symmetrical, left and right hand doors have the same cut out. This version features a lever to latch the strike in unlocked mode, and a holding function keeps the strike in unlocked mode even after removal of power, until the door is physically opened.

Available in unmonitored or monitored DC versions.

Application

This is a medium security strike suitable for use with standard mortise latch locks. It can also be adapted to become a surface mount unit for use with rim latch locks (such as Yale, Union, Chubb etc), by fitting it into rim case 71086.

Technical Information

Model	21086 SFP B H
Standard Operating Voltage	12V DC
Current Consumption	580mA (+/- 2.5%@12.5vdc)
Tolerance	+/- 1V
Keep	4mm horizontally adjustable
Holding force	350kgs
Dimensions of lock body	75x28x20mm
Face Plate	Anodised finish.
Handed	Non-Handed
Fail Safe or Fail Secure	Fail Secure
Holding function	Yes
Unsecure mode latch facility	Yes
Vital Parts	Hardened
Moving Parts	Self-Lubricating
Maintenance	Minimal
Fitting	Mortise Locks
Monitoring	No
Eff Eff equivalent	27eE