

Model:DS-7204HI-S(VS)**Name:7204 Series Network DVR****Parameters**

	DS-7204HI-S	DS-7204HI-VS
Video compression	H.264	
Preview resolution	PAL: 352×288 ; NTSC: 352×240	
Playback resolution	QCIF/CIF	
Video input	4	
Video input interface	BNC (Electrical Level: 1.0Vp-p, resistance: 75Ω)	
Composite video output	1 channel, BNC (Electrical Level: 1.0Vp-p, resistance: 75Ω)	
Spot video Output	1 channel, BNC (Electrical Level: 1.0Vp-p, resistance: 75Ω)	
Frame rate	PAL:1/16 to 25FPS, NTSC: 1/16 to 30FPS	
Audio compression	OggVorbis	
Audio compression rate	16Kbps	
Audio input	1	
Audio input interface	RCA (Electrical Level: 2.0Vp-p, Resistance: 1KΩ)	
Audio output	1 channel, RCA (Linear Electrical Level, Resistance: 600Ω)	
Stream type	Video/Video&Audio	
Bit rate	32Kbps to 2Mbps, self-defined	
HDD interface	1 SATA interface can support 1 SATA HDD up to2000GB in total	
Communication interface	1 RJ45 10M/100M self-adaptive Ethernet Interface 1 RS-485 interface	
USB interface	1 USB interface, USB2.0	
VGA interface	Unavailable	1 VGA interface can support resolution: 800×600/60Hz, 1024×768/60Hz, 1280 ×1024/60Hz
External alarm in	4	
Relay output	1	
Voice talk	1 channel, RCA (Electrical Level: 2.0Vp-p, Resistance: 1KΩ)	
Dual stream	Available	
Power supply	12VDC	
Power consumption	≤10W (without HDD)	
Operating temperature	-10℃ to +55℃	
Relative humidity	10% to 90%	
Size	315×230×45 mm	
Weight	< 8Kg (without HDD)	