

Model:DS-8000HCI-S

Name:DS-8000HCI-S Series Network DVR

Parameters

Model name	DS-8004HCI-S	DS-8008HCI-S	DS-8012HCI-S	DS-8016HCI-S
Video compression	H.264			
Preview resolution	4CIF real-time (PAL: 704*576, NTSC: 704*480)			
Playback resolution (PAL/NTSC)	QCIF&CIF real-time, 2CIF 12/13fps, DCIF 8/9 fps, 4CIF 6/7 fps			
Dual Playback	supported			
Video input	4	8	12	16
	BNC (1.0Vp-p, 75Ω)			
Main video output	1 channel, BNC (1.0Vp-p, 75Ω)			
Aux video output	-	1 channel, BNC (1.0Vp-p, 75Ω)		
Frame rate	PAL: 1/16~25FPS, NTSC: 1/16~30FPS			
Stream type	Video/ Video&Audio			
Dual stream	supported			
Max bit rate	32Kbps~2Mbps adjustable			
Audio input	4	8	12	16
	BNC (2.0Vp-p, 1kΩ)			
Main audio output	1 channel, BNC (Linear Electrical Level, 600Ω)			
Aux audio output	-	1 channel, BNC (Linear Electrical Level, 600Ω)		
Audio compression	OggVorbis, 16Kbps			
Audio	1 channel, BNC (Linear Electrical Level, 1KΩ)			
Voice talk	1 channel, BNC (Linear Electrical Level, 1KΩ)			
Communication interface	1 RJ45 10M/100M Self-adaptive Ethernet Interface 1 RJ45 RS-232 Port			
RS-485 Port	1 Port (T+, T-, R+, R-)			
Keyboard interface	2 RJ45	1 Port (D+, D-)		
SATA interface	4	8	8	8
USB interface	1 USB interface, USB1.1, can support USB flash memory, USB HDD, USB CD-R/W, USB DVD or USB mouse.			
VGA interface	1 VGA interface, support resolution: 800×600/60Hz, 800×600/75Hz, 1024×768/60Hz			
External alarm in	4	16	16	16
Relay output	2	4	4	4
Power supply	100~240VAC, 6.3A, 50~60Hz			
Power consumption	20~42W (without HDD and CD-R/W)			
Working temperature	-10°C to +55°C			
Working humidity	10% to 90%			
Size	19" Standard (450mm*450mm*95mm)			
Weight	≤ 17.6 pounds (8Kg). (without HDD and CD-R/W)			