Model:DS-8000HFI-S

Name:DS-8000HFI-S Series Network DVR

Parameters

Parameters	DS-8000HFI-S	
Video compression	H.264	
Preview resolution	4CIF real-time (PAL: 704*576, NTSC: 704*480)	
Playback resolution	4CIF/DCIF/2CIF/CIF/QCIF real-time	
Dual Playback	supported	
Video input	4/8/16 channels BNC (1.0Vp-p, 75Ω)	
Main video output	1 channel, BNC (1.0Vp-p, 75Ω)	
Aux video output	1 channel, BNC (1.0Vp-p, 75Ω)	
Frame rate	PAL: 1/16~25FPS, NTSC: 1/16~30FPS	
Stream type	Video/Video&Audio	
Dual stream	supported	
Max bit rate	32Kbps~2Mbps, self-define	
Audio input	4/8/16 channels BNC (2.0Vp-p, 1kΩ)	
Main audio output	1 channel, BNC (Linear Electrical Level, 600Ω)	
Aux audio output	1 channel, BNC (Linear Electrical Level, 600Ω)	
Audio compression	OggVorbis, 16Kbps	
Voice talk	1 channel, BNC (Linear Electrical Level, 1KΩ)	
Communication interface	1 RJ45 10M/100M Self-adaptive Ethernet Interface 1 RJ45 RS232 Port	
RS-485 Port	1 Port (T+, T-, R+, R-)	
Keyboard interface	2 RJ45	1 Port (D+, D-)
SATA interface	8 SATA interfaces, max support 8 SATA HDD. Each HDD can max support 2000GB	
USB interface	1 USB interface, USB1.1, can support USB flash memory, USB HDD and USB CD-R/W	
VGA interface	1 VGA interface, support resolution: 800×600/60Hz, 1024×768/60Hz, 1280×1024/60Hz	
External alarm in	16	
Relay output	4	
Power supply	100~240VAC, 6.3A, 50~60Hz	
Power consumption	20~42W (without HDD and CD-R/W)	
Working temperature	-10°C to +55°C	
Working humidity	10% to 90%	
Size	19” Standard (450mm*450mm*95mm)	
Weight	≤8Kg (without HDD and CD-R/W)	