

Model:DS-8000HSI-S

Name:DS-8000HSI-S Series Network DVR

Parameters

Model name	DS-8004HSI-S	DS-8008HSI-S	DS-8016HSI-S
Video standard	H.264		
Preview resolution	4CIF real-time (PAL: 704*576, NTSC: 704*480)		
Playback resolution (PAL/NTSC)	QCIF/CIF real-time 2CIF 15/16 FPS per channel DCIF 12/13 FPS per channel 4CIF 8/9 FPS per channel	QCIF/CIF real-time 2CIF 8/9 FPS per channel	
Video input	4	8	16
	BNC (1.0Vp-p, 75Ω)		
Video loop output	4	8	16
Composite video output	1 channel, BNC (1.0Vp-p, 75Ω)		
Aux video output	-		
Audio input	-		
Composite audio output	-		
Aux audio output	-		
Frame rate	PAL: 1/16~25FPS, NTSC: 1/16~30FPS		
Stream type	Video		
Max bit rate	32Kbps~2Mbps, self-define		
Dual stream	-		
Voice talk	-		
Network port	1 RJ45 10M/100M UTP port		
RS-232	1 RJ45 RS-232 port		
PTZ control	1 RS-485 port (T+, T-, R+, R-)		
Keyboard interface	2 RJ45 ports	1 port (D+, D-)	1 port (D+, D-)
SATA interface	4	8	8
E-SATA (optional)	1 st internal SATA interface can be extended to be E-SATA		
USB interface	1 USB 1.1 port		
VGA interface	1 VGA interface, support resolution: 800x600/60Hz, 1024x768/60Hz, 1280x1024/60Hz		
External alarm in	4	16	16
Relay output	2	4	4
Power supply	100~240VAC, 6.3A, 50~60Hz		
Power consumption	20 -- 42W (without HDD and CD-R/W)		
Working temperature	-10°C to +55°C		
Working humidity	10% to 90%		
Size	19" Standard (450mm*450mm*95mm)		

Weight	≤8Kg (without HDD and CD-R/W)
---------------	-------------------------------