

**Model:DS-2CC502/512/592P(N)(-A)**

**Name:Analog Dome Camera**

**Parameters**

<b>Parameter Model</b>	<b>DS-2CC502P(N)(-A)</b>	<b>DS-2CC512P(N)(-A)</b>	<b>DS-2CC592P(N)</b>
<b>Image Sensor</b>	1/3 inch SONY Super HAD CCD		
<b>Signal System</b>	PAL/NTSC		
<b>Effective Pixels</b>	PAL:500(H)×582(V) NTSC:510(H) ×492(V)	PAL:752(H) × 582 (V) NTSC:768(H) ×494(V)	PAL:752(H) × 582 (V) NTSC:768(H) ×494(V)
<b>Min. Illumination</b>	0.1Lux @ F1.2		
<b>Electronic Shutter</b>	1/50(1/60)s-1/100,000s		
<b>Day &amp; Night</b>	Electronic		
<b>Lens</b>	3.6mm@F2.0 (2.8mm,6mm,8mm option)		
<b>Horizontal Resolution</b>	420 TVL	480TVL	530TVL
<b>Synchronous</b>	Internal Synchronization		
<b>Video Output</b>	1Vpp Composite Output		
<b>S/N Ratio</b>	More than 48 dB		
<b>BLC</b>	ON		
<b>Working Temperature</b>	-10℃--60℃		
<b>Power Supply</b>	12VDC, ±10%, (-A)series support 24VAC/12VDC, ±10%		
<b>Power Consumption</b>	2W MAX		
<b>Dimension(mm)</b>	Φ138x87		
<b>Weight</b>	380g		