

Model:DS-2CD852F(-E)(-W)**Name:2 Mega CMOS Network Camera****Parameters**

Parameter Model	DS-2CD852F(-E)(-W)
Camera	
Image Sensor	1/3 inch CMOS
Effective Pixels	1600(H)×1200(V)
Lens Mount	C/CS mount
Auto Iris Lens	---
Lens	Option
Day&Night	Electronic
Min. Illumination	0.5Lux/F1.2 0.1Lux/F1.2, sensitization X5
Compression Standard	
Video Compression	MPEG-4
Video Output	32 K~2M, adjustable(8Mbps maximum)
Audio Compression	OggVorbis
Image	
Image Resolution	1600x1200,1280x720,800x600,704x576,640x480,528x384,704x288,352x288,176x144
Frame Rate	25fps(704x576), 12.5fps(1280x720), 5fps(1600x1200)
Functions	
Electronic PTZ	Support
Motion Detect	Support
Dual Stream	Support
SD Card Local Recording	Support
Heartbeat	Support
Password Protect	Support
Protocols	TCP/IP,UDP/IP,HTTP,FTP,SMTP,DHCP,DNS,DDNS,NTP,SNMP,RTP,RTCP,PPPoE. (-W) series support IEEE802.11g wireless WLAN criterion,2.4GHz frequency.
Interface	
Voice Talk Input	1 channel 3.5mm audio interface(2.0~2.4Vp-p,1kΩ)
Voice Output	1 channel 3.5mm audio interface(Line level, 600Ω)
Communication	1 RJ45 10M/100M self-adapted Ethernet port and, 1 RS-485 interface
Alarm Input	1 channel signal input
Alarm Output	1 channel signal on-off output
Others	

Working Temperature	-10°C-60°C
Power Supply	12VDC, ±10%, (-E) series support PoE (Power over Ethernet)
Power Consumption	3W MAX
Dimensions (mm)	63×59×116
Weight	650g