

**Model:DS-2CD852MF-E****Name:2 Mega Pixels Network Camera****Parameters**

Parameter Model	DS-2CD852MF-E
<b>Camera</b>	
Image Sensor	1/3 inch CMOS
Effective Pixels	1600(H)×1200(V)
Min. Illumination	0.5Lux/F1.2 0.1Lux/F1.2, sensitization X5
Electronic Shutter	---
Auto Iris Lens	---
Lens	Option
Lens Mount	C/CS mount
Day&Night	Electronic (ICR option)
S/N Ratio	More than 50dB
Video Output	1Vp-p Composite Output(75Ω/BNC)
<b>Compression Standard</b>	
Video Compression	MPEG-4
Video Output	32 K~2M, adjustable( 8Mbps maximum)
Audio Compression	OggVorbis
<b>Image</b>	
Image Resolution	1600x1200,1280x720,800x600,704x576,640x480,528x384,704x288,352x288,176x144
Frame Rate	25fps(704x576) 25fps(1280x720) 12.5fps(1600x1200)
<b>Functions</b>	
Electronic PTZ	Support
Motion Detect	Support
Dual Stream	Support
SD Card Local Recording	Support
Heartbeat	Support
Password Protect	Support
Protocols	TCP/IP,UDP/IP,HTTP,FTP,SMTP,DHCP,DNS,DDNS,NTP,SNMP,RTP,RTCP,PPPoE.
<b>Interface</b>	
Voice Talk Input	1 channel 3.5mm audio interface(2.0~2.4Vp-p,1kΩ)
Voice Output	1 channel 3.5mm audio interface(Line level, 600Ω)
Communication	1 RJ45 10M/100M self-adaptive Ethernet port and 1 RS-485 interface

Alarm Input	1 channel signal input
Alarm Output	1 channel signal on-off output
<b>Others</b>	
Working Temperature	-10°C-60°C
Power Supply	AC24V±10%/DC12V±10%, PoE (Power over Ethernet).
Power Consumption	4W MAX
Dimensions (mm)	69x63x157.5
Weight	600g